

EUROLUB FORMEL DX 5W-30

Description

FORMEL DX 5W-30 is a universal engine oil suitable for petrol and diesel engines in cars and vans, with or without turbochargers. It is particularly recommended for common-rail diesel engines in cars. The engine oil maintains the effectiveness of exhaust after-treatment systems over extended periods of use.

We also recommend it for vehicles requiring the following specifications:

Opel GM-LL-A-025, Opel GM-LL-B-025

Can be used with

ACEA C2 / C3
API SN / CF
VW 502.00
VW 505.00/505.01
MB 229.51 / MB 229.52
BMW Longlife-04
GM dexos2™
Renault RN0700/0710

Delivery

Art.-No. 244005	168 x 5 Liter	can
Art.-No. 244060	12 x 60 Liter	drum
Art.-No. 244208	2 x 208 Liter	drum

Technical Data

Data	Unit	Method	Value
Density at 15°C	kg/L	DIN 51 757	0.848
Viscosity at 40°C	mm ² /s	DIN 51 562	72.9
Viscosity at 100°C	mm ² /s	DIN 51 562	12.2
Viscosityindex (VI)	-	DIN ISO 2909	166
Flash point (COC)	°C	DIN ISO 2592	220
Pourpoint	°C	DIN ISO 3016	-39