

G-Energy Flushing Oil

G-Energy Flushing Oil is a highly effective flushing oil, designed for flushing of lubrication system of internal combustion engines of vehicles without disassembly, before changing of engine oil

Applications

- Intended for flushing of gasoline and diesel engines without disassembly, during the scheduled service of oil changes, after using oil with insufficient performance level or when the oil change deadline has been exceeded.
- Recommended for use in engines of LADA vehicles of PJSC "Avtovaz" production.
- To flush the engine, warm up the engine for 20-30 at idle, drain the old oil, pour in flushing oil and run the engine at idle for 15-25 minutes. Then drain the flushing oil, replace oil filter, and pour in fresh engine oil.

Advantages

- Quickly and effectively cleans engine parts from various types of deposits and mechanical impurities
- Compatible with the sealing materials
- Provides engine parts protection during flushing
- Does not affect on the oil performance, that is poured after flushing

Typical physical and chemical characteristics

Parameters	Value	Method
Kinematic Viscosity @100°C, mm ² /s	ASTM D 445	8,8
Flash Point (COC), °C	ASTM D 92	232
Pour Point, °C	GOST 20287	-33
Calcium, wt. %	ASTM D 6481	0,2
Zinc, wt. %	ASTM D 6481	0,07
Density @20°C, kg/m ³	ASTM D 4052	879

Specifications

- PJSC "Avtovaz"

The company's management system is certified in accordance with the international standards

ISO 9001



ISO 14001



ISO 45001

